

# MATERIAL SAFETY DATA SHEET

# GRANITE

GRANITE CONSTRUCTION INCORPORATED  
P. O. BOX 50085, WATSONVILLE, CA 95077-5085  
831-724-1011

PREPARED: 10-16-07  
REPLACES: 08-05-04

## SECTION I MATERIAL IDENTIFICATION

<b>CHEMICAL NAME</b> Not Applicable	<b>CHEMICAL FORMULA</b> Mixture	<b>MOLECULAR WEIGHT</b> Not Applicable
<b>TRADE NAME(S)</b> Asphalt-Rubber Binder		
<b>SYNONYMS</b> Rubberized Asphalt Binder		<b>DOT IDENTIFICATION NO.</b> 1999

## SECTION II PRODUCT AND COMPONENT DATA

COMPONENT(S) CHEMICAL NAME	CAS REGISTRY NO.	% (APPROX.) (optional)	OSHA PEL	ACGIH TLV
<b>Petroleum Asphalt, Rubberized</b>	<b>Mixture</b>	<b>100</b>	<b>See Section X</b>	<b>See Section X</b>
Petroleum Asphalt	8052-42-4	79-80	See Section X	See Section X
Petroleum Distillates (Naphthenic)	64742-11-6	2-3	See Section X	See Section X
Ground rubber	None	17-19	NE	NE

## SECTION III PHYSICAL DATA

<b>APPEARANCE AND ODOR</b> Viscous black liquid (when heated) with petroleum odor (liquid component is volatile)	<b>SOLUBILITY IN WATER</b> Not established		
<b>BOILING POINT</b>	NE	<b>SPECIFIC GRAVITY (H<sub>2</sub>O = 1 @ 39.2 F)</b>	NE
<b>VAPOR PRESSURE (mm Hg)</b>	NE	<b>MELTING POINT</b>	NE
<b>VAPOR DENSITY IN AIR (AIR = 1)</b>	NE	<b>EVAPORATION RATE (Butyl Acetate = 1)</b>	NE

## SECTION IV PHYSICAL HAZARDS (FIRE AND EXPLOSION HAZARD DATA)

<b>FLASHPOINT</b> (method used) NE (LIQUID COMPONENT IS COMBUSTIBLE)	<b>FLAMMABLE LIMITS IN AIR</b> (% Vol. in air) NE	<b>LEL</b> NE	<b>UEL</b> NE
---	--	------------------	------------------

### EXTINGUISHING AGENTS

Dry chemical, carbon dioxide or foam are preferred. Water fog may be used on flat surfaces such as roads.

### UNUSUAL FIRE AND EXPLOSION HAZARDS

Do not allow to heat above flash point. Volatile components can burn when supplied with an ignition source and can explode when concentrated above the LEL (e.g., in an enclosed environment). Never use welding or cutting torch on or near containers (especially empty) because vapors can ignite explosively.

Contact with powerful oxidizing agents may cause fire and/or explosion.

**SECTION V REACTIVITY DATA**

<b>STABILITY</b>	Unstable		<b>CONDITIONS TO AVOID</b> Keep away from ignition sources. Avoid contact with incompatible materials. Keep water out of hot asphalt.
	Stable	X	

**INCOMPATIBILITY (MATERIALS TO AVOID)**

May react with strong oxidizing agents. Contact with water may cause splashing of hot materials.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Normal combustion forms carbon dioxide and water vapor and may produce hydrogen sulfide and oxides of sulfur and nitrogen. Incomplete combustion may produce carbon monoxide.

<b>HAZARDOUS POLYMERIZATION</b>	May Occur		<b>CONDITIONS TO AVOID</b> Not applicable
	Will Not Occur	X	

**SECTION VI TOXICITY AND FIRST AID**

<b>PRIMARY ROUTE(S) OF EXPOSURE</b>	Inhalation? Yes	Skin? Yes	Ingestion? No
-------------------------------------	-----------------	-----------	---------------

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

**Eye Contact:** Heated material can cause severe thermal burns. Asphalt fumes may cause eye irritation. Exposure to hydrogen sulfide at concentrations above 4 ppm may cause eye irritation.

**Skin Contact:** Heated material can cause severe thermal burns. Emissions may cause mild irritation. Chronic exposure to petroleum asphalt has caused skin disorders such as dermatitis, folliculitis, or oil acne. There may be an increased sensitivity to sunburn when the skin is exposed to petroleum asphalt and asphalt emissions (fumes and vapors). Cutback asphalt oil contains petroleum oils similar to ones categorized by the IARC as causing skin cancer in mice. Some trace components (e.g. naphthalene, n-hexane and toluene) may be skin absorbed.

**Ingestion:** Direct contact with heated material can produce thermal burns on contacted tissues. Petroleum asphalt has a low toxicity when ingested. However, petroleum distillates may be absorbed from the gastrointestinal tract, with possible systemic effects (gastrointestinal irritation, vomiting, diarrhea, and CNS depression) and possible aspiration into the lungs. Aspiration of petroleum distillates has caused pulmonary edema and chemical pneumonitis.

**Inhalation:** Petroleum asphalt emissions (fumes and vapors) may have an unpleasant odor, and may produce nausea and irritation of the upper respiratory tract. Elevated concentrations of thermal decomposition products may result in various health effects, including respiratory irritation (nitrogen oxides, sulfur oxides, hydrogen sulfide, hydrocarbons), CNS depression (hydrocarbons) and chemical asphyxiation (carbon monoxide, hydrogen sulfide). Systemic effects associated with trace components (less than 1 percent) are not anticipated during normal use. Chronic exposure to elevated levels of asphalt emissions may result in chronic respiratory irritation and/or other lung disease.

<b>CARCINOGENICITY</b> Petroleum asphalt and the asphalt additives in this product are not listed on the NTP, IARC, or OSHA lists of carcinogens. The IARC has determined that there is sufficient evidence for the carcinogenicity of extracts of steam-refined bitumens, air refined bitumens and pooled mixtures of steam- and air-refined bitumens in experimental animals. Further, IARC has determined that there is limited evidence for the carcinogenicity of undiluted steam-refined bitumens in experimental animals. Also, IARC determined that there is inadequate evidence that bitumens alone are carcinogenic to humans. Some possible trace components (e.g., benzene, < 0.1 %) may be carcinogenic.	<b>NTP</b> NE	<b>IARC</b> NE	<b>OSHA</b> NE
<b>CALIFORNIA PROPOSITION 65 WARNING</b> "This product may contain chemical(s) known to the State of California to cause cancer."	<b>CA LISTED CARCINOGEN(S)</b> unknown		

**SIGNS AND SYMPTOMS OF EXPOSURE**

Symptoms of petroleum asphalt exposure include (but may not be limited to): irritation of the nose and throat, nausea, dizziness, eye irritation and dermatitis.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

Exposure to asphalt fumes and/or vapors may aggravate existing respiratory, skin and/or eye conditions.

**EMERGENCY AND FIRST AID**

**Eyes:** Flush eye(s) with plenty of water for 15 minutes, while holding eyelid(s) open. Beyond flushing, do not attempt to remove material from eyes except under medical supervision. Contact physician.

**Skin:** Hot Material- Remove contaminated clothing and immediately flush in cool water for at least 15 minutes. Apply iced water or cold packs to burned area if burned area is less than 10% of the body surface. Do not attempt to remove material from a burn. Get prompt medical attention. Cold Material- Clean exposed skin with oil-dissolving skin cleaner. Do not use solvents or thinners to remove material from skin.

**Ingestion:** Do not induce vomiting. If conscious, give large amounts of water. Contact a physician immediately.

**Dust inhalation:** Remove to fresh air if breathing is difficult. Get prompt medical attention if breathing remains difficult or if irritation persists.

**SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Personnel involved in cleanup processes should implement controls as identified in Section VIII as appropriate. Keep all ignition sources at least 50 feet away. Avoid personal contact with heated material. Prevent materials from entering streams, drainages, or sewers. Spills entering surface waters (or any other watercourse or sewers entering/leading to surface waters) that cause a sheen must be reported to the National Response Center 800/424-8802. None of the components in these products are subject to the reporting requirements of Title III of SARA, 1986, and 40 CFR 372.

**WASTE DISPOSAL METHOD**

Dispose of waste materials only in accordance with applicable federal, state, and local laws and regulations.

**STORAGE AND HANDLING PRECAUTIONS**

Store away from all ignition sources and open flames, in accordance with applicable laws and regulations. Storage containers should be ventilated to reduce fire and explosion hazard, and possible overexposure of personnel to fumes and vapors. Do not weld, heat, or drill container. Emptied container may contain hazardous material which may ignite explosively if heated sufficiently. Do not store near food and beverages or smoking material. Avoid incompatible materials. When petroleum asphalt products are heated, potentially irritating emissions (fumes, mists, vapors) may be released. Tripping accidents have occurred because of asphalt buildup on bottoms of shoes and boots. Materials should be removed regularly to prevent such accidents. See Section VIII for additional information.

**SECTION VIII PERSONAL PROTECTION AND CONTROL MEASURES****RESPIRATORY PROTECTION**

Not required under normal use and working conditions. For air contaminant concentrations which exceed or are likely to exceed applicable exposure limits, use a NIOSH-MSHA approved, contaminant-specific, air-purifying respirator. If such concentrations are sufficiently high that the air-purifying respirator is inadequate, or if oxygen adequate to sustain life is not present, use a positive pressure self-contained breathing apparatus. Consult an industrial hygienist for evaluation of exposures. Follow all applicable MSHA or OSHA respirator use, fitting, and training standards and regulations.

**VENTILATION**

Use only in well-ventilated areas. Natural ventilation generally adequate to maintain exposures below appropriate exposure limits under anticipated use conditions.

**Local Exhaust** As required

**Special**

**Mechanical (General)** As required

**Other**

**PROTECTIVE GLOVES**

Chemical resistant gloves for direct contact with product

**EYE PROTECTION**

Safety glasses with side shields should be worn as minimum protection. As needed, wear chemical safety goggles to prevent eye contact with product.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Protective clothing should be worn to prevent skin contact.

**HYGIENE**

Use normal good hygiene practices. Clothes saturated from contact with petroleum distillates should be removed promptly to prevent continued contact with skin. Wash hands with soap and water before eating, drinking, smoking, and using toilet facilities. Wash work clothes after each use. Clean skin with soap and water, or an oil-dissolving skin cleaner. Do not use solvents or thinners to remove material from skin.

**OTHER CONTROL MEASURES**

A fresh water supply for emergency first aid and washing facilities should be readily available. An oil-dissolving skin cleaner should be available. Workers should station themselves on the windward side of asphalt emissions when possible. Asphalt emission levels should be monitored as needed to evaluate exposures during handling and use of product, including activities which generate dust from hardened asphalt concrete. Exposures in excess of the PEL should be reduced to the lowest feasible level through engineering and administrative controls (such as source control, ventilation and/or work practice changes); respiratory protection should be used only where exposures continue to exceed applicable PEL(s).

**SECTION IX TRANSPORTATION****DOT HAZARD CLASS**

None

**PLACARD REQUIRED**

None

**LABEL REQUIRED**

If the shipping temperature of a solid equals or exceeds 464 °F, D.O.T. regulations classify the solid as an "Elevated Temperature Material", and a "HOT" label is required. Label as required by the OSHA and MSHA Hazard Communication standards [29 CFR 1910.1200 (f) and 30 CFR Part 42], and applicable state and local regulations.

**SECTION X EXPOSURE LIMITS**

<b>PETROLEUM ASPHALT (ASPHALT FUMES)</b>	<b>TWA</b>	<b>MSHA PEL</b>	<b>OSHA PEL</b>	<b>NIOSH REL</b>	<b>ACGIH TLV</b>
	<b>STEL</b>	NE	NE	NE	0.5 mg/m <sup>3</sup>
	<b>C</b>	NE	NE	5 mg/m <sup>3</sup>	NE
	<b>IDLH</b>	NE	NE	NE	NE
	<b>OTHER EXPOSURE LIMITS:</b> Cal/OSHA PEL – 5 mg/m <sup>3</sup> (TWA)				
<b>PETROLEUM DISTILLATES (NAPHTHA)</b>	<b>TWA</b>	<b>MSHA PEL</b>	<b>OSHA PEL</b>	<b>NIOSH REL</b>	<b>ACGIH TLV</b>
	<b>STEL</b>	NE	500 ppm	350 mg/m <sup>3</sup>	400 ppm
	<b>C</b>	NE	NE	NE	NE
	<b>IDLH</b>	NE	NE	1800 mg/m <sup>3</sup>	NE
	<b>OTHER EXPOSURE LIMITS:</b> Cal/OSHA PEL – 300 ppm (TWA), 400 ppm (STEL)				
<b>PETROLEUM DISTILLATES (OIL MIST)</b>	<b>TWA</b>	<b>MSHA PEL</b>	<b>OSHA PEL</b>	<b>NIOSH REL</b>	<b>ACGIH TLV</b>
	<b>STEL</b>	NE	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	NE
	<b>C</b>	NE	NE	10 mg/m <sup>3</sup>	NE
	<b>IDLH</b>	NE	NE	NE	NE
	<b>OTHER EXPOSURE LIMITS:</b> Cal/OSHA PEL – 5 mg/m <sup>3</sup> (TWA)				
<b>PETROLEUM DISTILLATES (KEROSENE, DIESEL)</b>	<b>TWA</b>	<b>MSHA PEL</b>	<b>OSHA PEL</b>	<b>NIOSH REL</b>	<b>ACGIH TLV</b>
	<b>STEL</b>	NE	NE	100 mg/m <sup>3</sup> (kerosene)	100 mg/m <sup>3</sup> (diesel) 200 mg/m <sup>3</sup> (kerosene)
	<b>C</b>	NE	NE	NE	NE
	<b>IDLH</b>	NE	NE	NE	NE
	<b>OTHER EXPOSURE LIMITS:</b> Cal/OSHA PEL – NE				

**NOTES**

PEL = permissible exposure limit  
 REL = recommended exposure limit  
 TLV = threshold limit value  
 % SiO<sub>2</sub> = percent silicon dioxide (silica) in dust

TWA = 8-hour time-weighted average  
 STEL = short-term exposure limit (15-minute average)  
 C = ceiling (peak exposure)  
 IDLH = immediately dangerous to life or health

ppm = parts per million in air  
 mg/m<sup>3</sup> = milligrams per cubic meter of air  
 NE = not established  
 NA = not applicable